


Search




ASME, 20", 6 Hold Down, 50 PSI MAWP, Model 8350 10"

- ASME SYMBOL & DATA PROVIDED
- THREADED HOLD-DOWNS
- 6" OR 10" HIGH COLLAR AVAILABLE

This Tiona 20" Full Opening Manhole conforms to the requirements of the ASME code for pressure vessels Section VIII, Division 1.

Assembly No.	Weld Collar	Cover	Wing-Nut, Swing Bolts Hinge Pins	Number Hold Downs	* Working Pressure	Weight
8350ASW-10"	Aluminum	Steel	Stnls 304	6	50 PSI 3.4 BAR	58 lb [26.4 kg]
8350ALW-10"	Aluminum	Stnls 316L	Stnls 304	6	50 PSI 3.4 BAR	58 lb [26.4 kg]
8350SCW-10"	Steel	Steel	Stnls 304	6	50 PSI 3.4 BAR	88 lb [40 kg]
8350LCW-10"	Stnls 316L	Stnls 316L	Stnls 304	6	50 PSI 3.4 BAR	88 lb [40 kg]

□



ASME Replacement Swing-bolt / Wing-nut Assemblies

[EB3-99](#): Installation and Care Instructions for Teflon Encapsulated Square Gaskets for Tiona-Betts Full Opening Manholes

[EB-07-03](#): Maintenance and Use of Betts Full Opening Pressure Manhole

